

# 4T 25W40 SL MARINE

Marine 4T 25W40 has been specially developed for blended marine engines using new generation additives. Suitable for Outboard and Inboard, latest generation gasoline engines, indirect or direct injection, supercharged, turbocharged or naturally aspirated, Outboards requiring an approved NMMA FC-WTM lubricant approval, Verado , Mercruiser , NISSAN Marine engines.

### Features and Benefits

- ✓ Provides full protection against soot formation.
- ✓ It lubricates the engine parts perfectly and ensures a fast and reliable start-up.
- ✓ It provides good compression with excellent cleaning properties.

### Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.150
Flash Point	ASTM D 92	Min.220°C
Pour Point	ASTM D97	Max .(-36°C)

### Approvals and Specifications

- ◆ API SL
- ◆ NMMA FC-W under n° FB-13800W
- ◆ MERCURY
- ◆ NISSAN MARINE

### Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).