

HYDRAULIC BRAKE DOT-4

It is a synthetic brake and clutch hydraulic fluid that provides excellent performance and increased braking safety at different temperatures. It shows high performance even at extreme temperatures caused by friction in brake systems. It is a synthetic brake fluid developed for the brake and clutch systems of all automobiles and motorcycles.

Features and Benefits

- ✓ While the product ensures that the system continues to operate in very cold weather, it prevents leakage and maintains fluidity in the system at high operating temperatures.
- ✓ It protects all the different metal components in the brake system against corrosion and prevents system failure.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	MIN.1.8 cSt
Density 15° C	ASTM D 4052	1.040-1.085 g/cm ³
Boiling point	ASTM D 1120	Min.250°C
Wet Boiling Point	SAE J1703	Min.155
pH	ASTM D 1287	7.4-9.4

HYDRAULIC BRAKE OIL

Approvals and Specifications

- ◆ SAE J1703
- ◆ SAE J1704
- ◆ FMVSS 116 DOT 4
- ◆ ISO 4925

Storage Information

- ✎ Packaging; It should be stored in covered areas with tightly closed lids.
- ✎ It should not be exposed to the direct effects of solar heat and heat sources.
- ✎ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ✎ For more information, refer to the Material Safety Data Sheet (MSDS).