

PLYWOOD MACHINE OIL

Wooden mold release oils are a product used in all kinds of concrete molds, except metal molds. By preventing the mold from sticking with fresh concrete, it enables the mold to be separated from the concrete surface more easily and you can obtain a smooth concrete with a smooth surface. It extends the life of the mould.

Features and Benefits

- ✓ It prevents the concrete from sticking to the molds by creating a thin film layer inside the mold.
- ✓ It enables smooth concrete surfaces to be obtained.
- ✓ It eliminates the need for mold cleaning and enables reuse.
- ✓ It increases the efficiency and lifespan of the mould.
- ✓ It is ready to use and its application is simple and easy.

Storage Information

- ✎ Packaging; It should be stored in covered areas with tightly closed lids.
- ✎ It should not be exposed to the direct effects of solar heat and heat sources.
- ✎ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ✎ For more information, refer to the Material Safety Data Sheet (MSDS).

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (40° C)	ASTM D 445	28.8-35.2 cSt
Viscosity Index	ASTM D 2270	Min.90
Flash Point	ASTM D 92	Min.170°C
Pour Point	ASTM D97	Max .(-25°C)