

## PREMIUM 5W40 SN/CF

It is a low viscosity, high stability engine oil produced as a result of the perfect blend of new generation additives and fully synthetic oils. It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear. In addition to its excellent lubrication and anti-corrosion properties in a wide temperature range, it provides superior and long-lasting engine protection thanks to its formula developed with anti-wear technology. It is recommended for use in all operating conditions, especially in stop-and-go and heavy city traffic.

### Features and Benefits

- ✓ It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear.
- ✓ In addition to its excellent lubrication and anti-corrosion properties in a wide temperature range, it provides superior and long-lasting engine protection thanks to its formula developed with anti-wear technology.

### Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.155
Flash Point	ASTM D 92	Min.215°C
Pour Point	ASTM D97	Max .(-35°C)

## ENGINE OIL

### Approvals and Specifications

- ◆ API SN/SL
- ◆ API C.F.
- ◆ ACEA A3 / B3-12 / B4-12
- ◆ MB 229.5, 229.3, 229.1 (v2012.2)
- ◆ VW 502.00 / 505.00
- ◆ Renault RN 700 / 710
- ◆ Opel GM-LL-B-025
- ◆ JASO MA2 (T903-2011)

### Storage Information

- ☞ Packaging: It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).