

PROFESSIONAL 10W40 SM/CF

ENGINE OIL

It is a semi-synthetic engine oil produced by blending synthetic and high-quality base oils with advanced technology additives to meet the lubrication needs of LPG engines. It is recommended for use in the engines of all gasoline, diesel and LPG passenger cars, pickup trucks and minibuses, and small commercial vehicles.

Features and Benefits

- ☑ It significantly prevents friction losses and deposit formation in the engine and provides resistance to wear .
- ☑ Superior and long - lasting properties thanks to its formula developed with anti - wear technology as well as excellent lubrication and corrosion prevention properties in a wide temperature range . Provides long - lasting engine protection .

Technical specifications

TEST	METHOD	VALUE
K.Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.130
flash point	ASTM D 92	Min.220°C
Pour Point	ASTM D97	Max .(-30°C)

Approvals and Specifications

- ◆ API SL/CF
- ◆ API SM/CF
- ◆ VW 501.01 / 505.00
- ◆ ACEA A3/B3-04
- ◆ ACEA A3/B4-04
- ◆ MB Approval 229.1
- ◆ AVTOVAZ LADA cars

Storage Information

- ☞ Packaging: It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).