

PROFESSIONAL 10W60 SL/CF

ENGINE OIL

It is an engine oil reinforced with advanced additives, formulated for the special needs of old vehicles that have exceeded 150,000 km. 10W-60 is also suitable for high performance and motorsport applications requiring high viscosity engine oil.

Features and Benefits

- ✓ It provides resistance to the engine warming up and starting easily in cold weather and against thinning in very hot weather, thus preventing any problems in the engine.
- ✓ It keeps the engine clean with the superior dispersant and detergent additives it contains. Clean parts work better and provide high performance.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	21.9-27.5 cSt
Viscosity Index	ASTM D 2270	Min.155
Flash Point	ASTM D 92	Min.215°C
Pour Point	ASTM D97	Max .(-30°C)

Approvals and Specifications

- ◆ API C.F.
- ◆ MB 229.1
- ◆ API SN/SM
- ◆ API SL/SJ
- ◆ ACEA A3/B3
- ◆ ACEA A3/B4-1

Storage Information

- ☞ Packaging; It should be stored in covered areas with tightly closed lids.
- ☞ It should not be exposed to the direct effects of solar heat and heat sources.
- ☞ exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- ☞ For more information, refer to the Material Safety Data Sheet (MSDS).