

PROFESSIONAL TRACTOR OIL 426

It is an extra high performance, multi-purpose tractor oil designed to meet the requirements of hydraulic and transmission parts manufacturers. Designed to maximize the performance of agricultural and commercial tractors.

Features and Benefits

- Thanks to its high viscosity index, it performs effectively even under very cold weather conditions.
- ✓ It ensures high efficiency and quiet operation of the brake system with its friction modifier additive.
- With its specially developed formula, it provides a long service life by keeping rust, corrosion and foam formation under control.
- Thanks to its high thermal and oxidation stability, it prevents deposit formation and increases operating efficiency.

Technical specifications

| TEST | METHOD | VALUE |
|--------------------------------|----------------|---------------|
| ISO GARD | | 10W30 |
| Kinematic Viscosity (100°C) | ASTM D 445 | 9.3-12.5 cSt |
| Viscosity Index | ASTM D 2270 | Min.140 |
| Flash Point | ASTM D 92 | Min.220°C |
| Pour Point | ASTM D97 | Max .(-36°C) |

TRACTOR TRANSMISSION OIL

Approvals and Specifications

- ♦ Allison C-4
- ♦ API GL-4
- ♦ Caterpillar TO-2
- CNH MAT 3505
- CNH MAT 3525
- Denison UTTO/THF
- FORD NH FNHA-2-C-201.00
- FORD ESN-M2C134-D
- ♦ JICASE MS 1204
- JOHN DEERE JDM J20D
- MASSEY FERGUSON CMS M1145
- MASSEY FERGUSON CMS M1143
- MASSEY FERGUSON CMS M1135
- New Holland WB NWH 410B
- AGCO Powerfluid 821

Storage Information

- Packaging; It should be stored in covered areas with tightly closed lids.
- It should not be exposed to the direct effects of solar heat and heat sources.
- exceed 60°C . It should be stored with a maximum of two pallets on top of each other.
- For more information, refer to the Material Safety Data Sheet (MSDS).

🛞 www.raschlubricant.com

+90 262 206 01 01

= +90 262 206 01 02

m İnönü Mah. San. 32. Sok. No:11, 41400 İnönü Gebze