

KORAL 4T 15W40 SL

Specially designed for modern, high-performance and four-stroke motorcycle users. It reduces high pressure and friction losses in the engine and provides excellent acceleration and power under race track conditions.

Features and Benefits

- Provides excellent protection against sediment, sludge and oxidation.
- Air absorption and foam formation are minimized even under the most severe operating conditions.
- Thanks to its special formulation, this oil provides excellent protection for gearboxes and wet clutches.
- It quickly provides a solid lubricant film for optimum protection of the engine at low temperatures and cold starts.

Technical specifications

TEST	METHOD	VALUES
Kinematic Viscosity (100° C)	ASTM D 445	12.5-16.3 cSt
Viscosity Index	ASTM D 2270	Min.110
Flash Point	ASTM D 92	Min.215°C
Pour Point	ASTM D97	Max .(-25°C)

MOTORCYLE OIL

Approvals and Specifications

- ♦ API SL
- JASO MA-2

Storage Information

- $\begin{tabular}{c} \end{tabular}$ Packaging; It should be stored in covered areas with tightly closed lids.
- It should not be exposed to the direct effects of solar heat and heat sources.
- exceed 60°C. It should be stored with a maximum of two pallets on top of each other.
- For more information, refer to the Material Safety Data Sheet (MSDS).