

TRANSPARENT LIQUID GREASE SPRAY

It is a transparent, multi-purpose lubricant. It is resistant to friction and water, fluid and non-sticky. It is a highly efficient corrosion inhibitor. With its composition containing special oils and additives, it quickly penetrates and adheres to the surface. It can be used safely on all kinds of surfaces that require lubrication at home and at work, in many industrial areas such as heavy machinery and forklifts, sprocket chain systems.

Features and Benefits

- It extends the life of the parts. It ensures quiet and efficient operation.
- It is a highly efficient lubricant and corrosion inhibitor.
- It is resistant to high pressure.
- Resistant to corrosion, water and 180°C temperature.
- It has much higher adhesion properties.
- It does not flow or drip. It provides transparent and permanent lubrication.

Technical specifications

Met hod	Value
Density	0.75-0.85 g/ cm ³
Viscosity	2 -10 mPa.s
Physical appearance	Aerosol
Smell	Characteristic

Storage Information

Attention! The box is pressurized. Do not drill, including empty boxes. Do not expose to temperatures above 50°C and direct sunlight, do not throw into fire, fire or welding etc. Do not spray on incandescent objects. Do not smoke while using. Use in open areas or well-ventilated environments, accompanied by appropriate PPE, do not inhale for a long time. Keep out of reach of children.

First aid! In case of contact with eyes and skin, rinse with plenty of water for 15 minutes. Wash it. In case of excessive exposure to inhalation or ingestion, move the patient to a ventilated place, do not induce vomiting, and inform the healthcare personnel immediately. See MSDS for detailed information.